

18000 BTU / H CASSETTE

SUBMITTAL DATA: TM18HBKDI Job Name Location Date Purchaser Engineer Submitted To For Reference Approval Construction Unit Designation Schedule No.



TM18HBKDI





XK19

GENERAL FEATURES

- AHRI Certificate: See Matching or Paired Outdoor Unit AHRI Certificate
- Compact and Quiet Design
- 4 Way Discharge Air
- Internal Condensate Drain Pump
- Wireless Remote with LCD Display Included
- XK19 Wired Controller Included
- Low Ambient Cooling Based on Outdoor Unit Performance
- Low Ambient Heating Based on Outdoor Unit Performance
- Copper Tube / Aluminum Fin Coil (Blue Fin) 500 Hrs Salt Spray Tested

SYSTEM I	PERFORMANCE		
Cooling	Rated Capacity @ 95°F	Btu/h	See Outdoor Unit Submittals -Connected Unit Capaci
	Min-Max Capacity	Btu/h	5100 - 23200
Heating	Rated Capacity @ 47°F	Btu/h	See Outdoor Unit Submittals -Connected Unit Capaci
	Min-Max Capacity	Btu/h	5800 - 23500
SEER / EER			Based on Outdoor Unit Performance
HSPF / CO)P		Based on Outdoor Unit Performance
Energy St	ar®		Based on Outdoor Unit Performance
Cooling Temperature Range		°F	Based on Outdoor Unit Performance
Heating Temperature Range		°F	Based on Outdoor Unit Performance
INDOOR UNIT			TM18HBKDI
Fan Motor Output Power		W	45
Fan Motor FLA		amps	0.5
Air Flow (Min - Max)		CFM	265 - 418
Sound Pressure Level (Cooling / Heating)		dB(A)	35 - 47
Dehumidification		pt/hr	3.8
Condensate Drain Size (OD)		in	1
Unit Dimension (WxHxD)		in	23 1/2 X 23 1/2 X 9 1/2
Package Dimension (WxHxD)		in	30 1/2 X 29 X 11 1/4
Weight (Net / Gross)		lbs	44 / 53
REFRIGE	RANT PIPING		
Line Set Size (Liquid - Gas)		in	1/4 - 1/2
Pre-Charge Lengh		ft	Based on Outdoor Unit
Pipe Length (Min - Max)		ft	Based on Outdoor Unit
Max. Pipe Elevation		ft	Based on Outdoor Unit
ELECTRIC	AL		
Power Supply (Voltage Operating Range)		Powered by Outdoor Unit	
Rated Current (Cooling / Heating)		amps	Based on Outdoor Unit
MCA / MOCP		amps	Based on Outdoor Unit
Main Power Wire Size		AWG	Size Per Local Code
Interconnecting Wire Size		AWG	14 / 4













FEATURES & FUNCTION SUMMARY: TM18HBKDI

REMOTE CONTROLLER FUNCTIONS			
Auto Mode	Yes		
Auto Fan	Yes		
Auto Swing (Horizontal Auto Swing)	No		
Auto Swing (Vertical Auto Swing)	Yes		
Clock	Yes		
Dry Mode	Yes		
Dry Anti- Mildew (X- Fan) Mode	Yes		
Energy Saving Mode	Yes		
Dirty Filter Alert	No		
Fan Speed Control (7 Speeds)	Yes		
I Feel Function	Yes		
Privacy Lock	Yes		
Quiet Mode	No		
Room Temperature Display	No		
Sleep Mode	Yes		
Normal Sleep Mode Option	Yes		
Timer Mode	Yes		
Turbo Mode	Yes		
Display On/Off Control	Yes		
Freeze Guard Mode	Yes		
Power Failure Mode	Yes		













DIMENSIONS & CLEARANCES: TM18HBKDI













